



amesys
BEN

BLIND ANTHEA

ELECTROMAGNETIC SPEED LOG



ANTHEA Blind Version consists of:

- One IP65 metal case,
- One 48mm sensor that can be dismantled when ship is afloat, including a 16m cable,
- One weldable or screw-on-type hullfitting with valve.

The ANTHEA E/M log is suitable with the following BEN sensors :

- 48.1.RVB.16 sensor with weldable or screw-on type hullfitting with valve,
- 48.1.RVB watertight sensor with weldable or screw-on-type hullfitting with valve,
- 48.1.RB.16 sensor with weldable or screw-on-type hullfitting without valve,
- 48.1.RA (alu) sensor with aluminium weldable hullfitting without valve,
- Lens sensor for double hull ships.

MAIN FEATURES

- Simple configuration via a software "BLASS":
 - Calibration,
 - Correction of 3-points-linearization,
 - Display of error messages,
 - Alarm threshold adjustment,
 - Memorization of vessel settings.
- Automatic gain control.
- Damping control, via strap.
- 3-points-linearization.
- Permanent self-test.


ANTHEA BLIND is compatible with all navigation peripherals.

SPECIFICATIONS


- Dimensions : 244 x 164 x 95 mm,
- Weight: 3 kg,
- Power supply : 24 Vdc or 220 Vac – 50 or 60 Hz,
- Outputs :
 - 2 x 1/200 mile (relay outputs 24 V – 250 mA),
 - 1 x 1/10 mile (open collector),
 - 2 alarm outputs (relay outputs 50 V-2A),
 - 1 analog output (0-500 μ A),
 - 1 RS232 output- NMEA0183 format
- Scale : double scale : -2/+25 and -5/+50 knots,
- Distance : 0-99999,9 nautic miles.
- Speed accuracy : 0,5 % of full scale
- Distance accuracy : > 0,1 mile/hour.
- Damping : 4s, 16s or 32s.

OPTIONS

- Speed and distance analog repeater : GA120
- X/Y Sensor (65 mm diameter)
- LCD Graphic repeater (speed and distance) RGD100 incl. brightness control.



**CE Type approved to EMC European Directive
IEC 945 + IEC 1023**



NORMES

- CEI 945 according to IMO A.574
- CEI 1023 according to IMO A.478
- Hullfitting 48mm BV approved / Hullfitting 48.1.RVI GL approved / Hullfitting Lens GL & DNV approved.
- ANTHEA & RGD100 are E.C. type approved.

THIS DATA SHEET IS SUBJECT TO ALTERATION WITHOUT NOTICE

DOC048-B

